TOSHIBA

Color MFP

e-STUDIO 6527AC/7527AC

Introducing a new generation of Toshiba departmental MFPs – with high-performance, zero-trust security and cloud-ready features, these printers are the perfect choice for today's modern work environments.

- Highly Productive Color MFPs
- High-speed – 65 & 75 PPM Color and 75 & 85 PPM Black & White
- Leading-edge Security Features
- Cloud Print & Service Capabilities
- Built-in Optical Character Recognition



e-STUDIO™6527AC/7527AC

MAIN SPECIFICATIONS

Copy System	Indirect Electrostatic Photographic/OPC/Laser Printing/Heat Roller Fusing
Display	10.1" Color WSVGA Touch Screen Tilting Display
Copy Speed	Color: 65/75 PPM (LT), Monochrome: 75/85 PPM (LT)
First Copy Out	Color: 6.4/5.4, Monochrome: 4.5/4.1 Seconds
Warm-Up Time	From Powering On: Approx. 20 Seconds From Sleep & Low Power: Less Than 15.4 Seconds
Copy Resolution	600 x 600 dpi
Stack Feed Bypass	3.9" x 5.8" to 12" x 18", 12" x 47" Banner, Envelope
Multiple Copying	Up to 999 Copies
Paper Capacity	Four Drawer Version: Standard 2,280 Sheets/Max. 6,780 Sheets Tandem Drawer Version: Standard 3,520 Sheets/Max. 8,020 Sheets
Original Feed	300-Sheet DSDF with Double Feed Detection
Max. Original Size	LD/A3
Paper Feed Sizes	Drawers : 540 Sheets-ST-R to 12" x 18" Integral Tandem LCF: 1,160 x 2 LT Only Stack Feed Bypass: 120 Sheets-3.9" x 5.8" to 13" x 19", 12" x 47" Banner Opt. 2,500-Sheet External LCF LT Only Opt. 2,000-Sheet Piggyback External LCF LT Only
Paper Weights	Drawers: Standard: 540 Sheets x 4-16lb Bond-110lb Cover Tandem LCF 1,160 Sheets x 2-16lb Bond-110lb Cover Plus 540 Sheets x 2-16lb Bond-110lb Cover Stack Feed Bypass: 120 Sheets-16lb Bond-110lb Cover Opt. 2,500-Sheet External LCF LT Only-16lb Bond-110lb Cover Opt. 2,000-Sheet Piggyback External LCF LT Only-16lb Bond-110lb Cover
Duplex	Standard Automatic Duplex Unit (16lb Bond-140lb Index)
Reproduction Ratio	25% to 400%
Max Duty Cycle	540K/600K Month (Color: 100%)
Weight	Approx.470lb
Approx. Dimensions	37.6" (W) x 27.5" (D) x 48.3" (H)
CMYK Toner Yield	CMY: 39,200, K: 106,600 @ 5%
Power Source	120 Volts, 50/60 Hz, 16 Amps
Power Consumption	Maximum 2.0kW/2.4kW (120V)
Plug Type	NEMA 5-20
Memory	6GB
Hard Disk Drive	128GB Solid State Drive (SSD)

e-BRIDGE NEXT PRINT SPECIFICATIONS

PDL	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Resolution	600 x 600 dpi, 1,200 x 1,200 dpi or 3,600 (Equivalence) x 1,200 dpi (BW/with Smoothing) (PS3 Only)
Operating Systems	Windows® 8.1,10, 11, Windows Server® 2012/R2, Windows Server® 2016/19/22, Macintosh® (macOS X 10.10-15, 12), Unix®, Linux®
Network Protocols	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh Environments
Printing Protocols	SMB V1-3, LPR/LPD, IPP V1.2 w/Authentication (TLS 1.2/1.3), AppleTalk® PAP or EtherTalk, Port 9100 (Bi-Directional), NetWare P-SERVER LPD w/iPrint, Bluetooth (HCRP/BIP/OPP/FTP), WS Print, FTP
Print Drivers	Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016/19/22, Windows® 10, 11 (64-bit), macOS X 10.12-15, 11, 12
Interface	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed) Optional IEEE802.11b/g/n, Wireless LAN, Optional Bluetooth
Wireless Device	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
Device Management	TopAccess
Account Control	Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® Domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
Accessibility Features	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout, Audible Beeps, Optional Voice Assist

Security Features	User Authentication, Trusted Platform Module, On-Board Data Scramble Function, SCEP, Disable, e-Filing, Disable Copy, Disk Overwrite* , IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware Update, Integrity Check Function, Image Log, Card Authentication, Biometric Authentication *Conformance with HCD-PPv1.0 in High Security Mode
Environmental Standards	ENERGY STAR® (V3.1), EPEAT Gold, Californian Proposition 65
Certifications	WHQL (Windows® 8, 8.1, 10, 11, 2012, 2012 R2, 2016/19/22), Novell®, Citrix®, SAP, AirPrint® and Mopria®

SCAN SPECIFICATIONS

Scan Speed	DSDF Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color)
Scan Weights	9.3-110lb Bond RADF Scan: Simplex: 9.3-41.8lb Bond, Duplex: 13.3-41.8lb Bond
Scan Modes	Standard: Full Color, Auto Color, Monochrome, Grayscale
OCR	DOC/XLS/PPT/PDF
Scan Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
File Formats	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Slim PDF, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX
Image Compression	Color/Grayscale: JPEG (High, Middle, Low)

FACSIMILE SPECIFICATIONS

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	Up to 33.6 Kbps
Memory Transmission	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
Scan Speed	0.7 Seconds Per Page, Maximum 73 IPM

e-FILING SPECIFICATIONS

Operation Method	Color Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

ACCESSORIES (OPTIONS)

Additional Paper Options	
Large Capacity Feeder - 2,500 Sheet	MP2503L
Large Capacity Feeder - 2,000 Sheet	MP2002L
LCF Connector (to Add 2K LCF)	KN9000
Finishing Options	
65-Sheet Staple Finisher	MJ1115
65-Sheet Saddle-Stitch Finisher	MJ1116
Hole Punch for MJ1115/MJ1116	MJ6108N
Exit Tray	K6551
Connectivity/Security Options	
FAX Unit/2nd Line for FAX Unit	GD1370N
Wireless LAN/Bluetooth	GN4030A3
Fax Over IP License Key	GS1100NODE
Bluetooth Keyboard	GR9001
2nd NIC Holder	GR1430
USB Hub	GR1420
Meta Scan Enabler	GS1010NODE
Security SSD (512GB)	GE1280
FIPS HDD (320GB)	GE1260
Miscellaneous Options	
Card Reader Holder	GR1320
Accessory Tray	GR1330
Panel 10-Key Option	GR1340
Manual Pocket	KK5008
Harness for Coin Controller	GQ1280
Accessible Arm	KK2560

Software Options	
e-BRIDGE Global Print	GB2550NODE
IPSec Enabler	GP1080NODE
Unicode Font Enabler	GS1007NODE
Multi-Station Print Enabler Per Seat License	GS1090NODE
e-BRIDGE Plus for OneDrive for Business V3.0	GB2300NODE
e-BRIDGE Plus for SharePoint Online V3.0	GB2310NODE
e-BRIDGE Plus for Exchange Online V3.0	GB2320NODE
Workplace Productivity Bundle	GB2330NODE
e-BRIDGE Plus for Gmail	GB2380NODE
e-BRIDGE Plus for Google Workspace	GB2390NODE
e-BRIDGE Plus Voice Guidance	GB2540NODE

Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

© 2023 Toshiba America Business Solutions, Inc. Electronic Imaging Division
Inv. Code 22426 6527AC/7527AC Spec Sheet 5K PG 3/23

Corporate Office	25530 Commercentre Drive, Lake Forest, CA 92630 Tel: 949-462-6000
East Coast	959 Route 46 East, 5th Floor, Parsippany, NJ 07054 Tel: 973-316-2700
Midwest	8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631 Tel: 773-380-6000
South	2037 Bakers Mill Rd., Dacula, GA 30019 Tel: 678-546-9385
West Coast	25530 Commercentre Drive, Lake Forest, CA 92630 Tel: 949-462-6000
Website	business.toshiba.com